

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 December 2000 (14.12.2000)

PCT

(10) International Publication Number
WO 00/76015 A1

(51) International Patent Classification⁷: **H01M 8/10**,
8/12, 8/16

(74) Agents: HUNTSMAN, Peter, Harold et al.; Davies Col-
lison Cave, 1 Little Collins Street, Melbourne, Victoria 3000
(AU).

(21) International Application Number: PCT/AU00/00631

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE,
DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU,
ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,
LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO,
NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR,
TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 2 June 2000 (02.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PQ 0788 4 June 1999 (04.06.1999) AU

(71) Applicant (*for all designated States except US*): CE-
RAMIC FUEL CELLS LIMITED [AU/AU]; 170
Browns Road, Noble Park, Victoria 3174 (AU).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(72) Inventor; and
(75) Inventor/Applicant (*for US only*): JAFFREY, Donald
[AU/AU]; 2 Bonnieview Road, Mount Dandenong, Victo-
ria 3767 (AU).

(54) Title: A FUEL CELL GAS SEPARATOR



(57) Abstract: A fuel cell gas separator member (10) comprises a layer (22) of copper or copper-based alloy having a layer (29) of oxidation-resistant material such as Al₂O₃ on the cathode side (30). A protective layer (31) may also be provided on the anode-side (26) of the copper or copper-based alloy layer. The copper-based alloy may be aluminium bronze in which case the oxidation-resistant layer may form automatically. Alternatively, the copper or copper-based alloy layer (22) may be wrapped in a foil (29, 31) of heat resistant steel. Other possibilities are disclosed.

WO 00/76015 A1